

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 July 2005 (07.07.2005)


PCT

(10) International Publication Number
WO 2005/062275 A1

- (51) International Patent Classification: G08G 1/052, 1/01
- (21) International Application Number: PCT/AU2004/001815
- (22) International Filing Date: 21 December 2004 (21.12.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2003907181 24 December 2003 (24.12.2003) AU
- (71) Applicant (for all designated States except US): RED-FLEX TRAFFIC SYSTEMS PTY LTD [AU/AU]; 31 Market Street, South Melbourne, Victoria 3205 (AU).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ONEA, Adrian [AU/AU]; 30 Bridge Street, Brighton, Victoria 3185 (AU). FIUSCO, Ricardo, John [AU/AU]; 6 George Street, Ashwood, Victoria 3147 (AU).
- (74) Agent: PHILLIPS ORMONDE & FITZPATRICK; 367 Collins Street, Melbourne, Victoria 3000 (AU).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

(Continued on next page)

(54) Title: VEHICLE SPEED DETERMINATION SYSTEM AND METHOD



LEGEND

- P1 Piezoelectric Sensor 1
P2 Piezoelectric Sensor 2
Loop Inductive Loop
T1 Time when Front Axle triggers P1
T2 Time when Front Axle triggers P2
T3 Time when Rear Axle triggers P1
T4 Time when Rear Axle triggers P2
 Δt_1 Time Interval used to measure the Speed of the Front Axle (T2-T1)
 Δt_2 Time Interval used to measure the Speed of the Rear Axle (T3-T2)
 Δt_3 Time Interval used to measure the Wheel Base (T3-T2)
 c_1 Count Speed 1 is the Number of Interval Counts between T2 and T1 ($\Delta t_1 \cdot \text{freq}$)
 c_2 Count Speed 2 is the Number of Interval Counts between T4 and T3 ($\Delta t_2 \cdot \text{freq}$)
 c_{wb} Count Speed Wheel Base is the Number of Interval Counts between T3 and T2 ($\Delta t_3 \cdot \text{freq}$)
 freq Reference Crystal Frequency
 c Distance separating P1 and P2

(57) Abstract: A method for verifying the speed of a vehicle having at least a front axle and a rear axle, using sensors separated by a distance. The presence of the vehicle is sensed and an image of the vehicle is recorded to enable the vehicle to be identified. The signals sensors are triggered to emit signals which are received by the system to enable the speed of the vehicle to be determined. The signals are also used to determine a wheel base measurement for the vehicle. The determined wheel base measurement is compared to an actual wheel base measurement of the vehicle being sensed and any discrepancy between them is taken to be indicative of potential errors in the speed of the vehicle determined by the method. In one embodiment, a database is provided, the database containing data relating to various vehicle types associated with vehicle specifications including a validated wheel base measurement for each vehicle type.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.